

IY204



Unbalanced Stereo Patch Cable - IY204



- extremely flexible
- compact construction (4.0 mm x 8.0 mm)

	Conductor	stranded bare copper, 7 x 0.20 mm	Leiteraufbau	blanke Cu-Litze, 7 x 0.20 mm
	Cross Section	0.22 mm ²	Leiterquerschnitt	0.22 mm ²
	Core Insulation	PE	Aderisolation	PE
	Single Core Shielding	bare copper spiral shield	Einzeladerabschirmung	blanker Cu-Wendelschirm
	No. of Cores	2	Aderanzahl	2
	Core Arrangement	parallel, separable	Aderanordnung	parallel, aufreißbar
	Outer Jacket	PVC, matt	Außenmantel	PVC, matt
	Dimensions	4,0 x 8,0 mm	Abmessungen	4,0 x 8,0 mm
	Min. Bending Radius	20 mm	Min. Biegeradius	20 mm
	Working Temperature	-20 °C / +70 °C	Betriebstemperatur	-20 °C / +70 °C
	Conductor Resistance	< 85 Ω/km	Leiterwiderstand	< 85 Ω/km
	Capacitance	130 pF/m	Kapazität	130 pF/m
	Insulation Resistance	> 1 GΩ x km	Isolationswiderstand	> 1 GΩ x km

■ black

Order Code Bestell-Nr.	Colour Farbe	Weight Gewicht	Standard Length Standardlängen	Max. Length / Reel Max. Länge / Spule
IY204	black	40 g/m	100 / 500 m	1000 m