

SAL MEDIATORE



Power Amplifier 150

Mono power amplifier for operation directly adjacent to an acoustic converter, for loudspeakers with critical impedance performance.

SAL

Uncompromising quality for reproduction par excellence. High tech from Germany.



M E D I A T O R E

Technical data:

Output measured at THD of 0.1 %:	8 Ohm 150 Watt
from 20 Hz to 20 kHz (undistorted	4 Ohm 220 Watt
musical performance up to	2 Ohm 250 Watt
1.5 times nominal power)	
Max. output current:	peaks: approx. 30 A
	continuous operation: 15 A
Signal-to-noise ratio:	20 Hz to 20 kHz > 83 dB
	Awtd > 88 dB
Input resistance:	12 kOhm
Input voltage:	1.5 V
Rise and fall times:	< 2.5 µs for all loads
Damping factor:	> 400
Frequency response at 1 W / 8 Ohm:	DC up to 100 kHz - 3 dB
Thermal fuse actuation temperature:	70°C
Rise delay time:	approx. 5 secs.
Max. input power:	approx. 500 W
Weight:	approx. 11 kg
Dimensions: (w x h x d)	220 x 115 x 340 mm

Subsonic, D.C. and thermal protection, min. ambient temperature 0° C, max. 40° C.

Power Amplifier 150

Mono power amplifier for operation directly adjacent to an acoustic converter, for loudspeakers with critical impedance performance.

What they say about it:

"...best performance figures".

"...extremely high damping factor guaranteed..."

The Power Amplifier 150 was put through its paces in:

Stereoplay Issue 8 / 1992

© 1994. All rights reserved. Copying or electronic processing of all or part of this brochure is only permissible with written permission. We reserve the right to make technical alterations and make no guarantee regarding the correctness of the information contained in this brochure. No liability is accepted for damages arising out of information which is incorrect. Valid 07/94